



TECHNICAL INFORMATION

Watts:	10
Lumens:	1100
Long Life:	20,000 Hours
Unit Color:	Black
Body Type:	ABS + PC + Aluminium
LED Chip Type:	SMD
CRI:	>80
Dimmable:	No
Beam Angle:	90°
Color Temperature:	4000K
Dimension:	231.9x166.3x33.5mm
Sensor Type:	PIR
Detection Distance:	8Mtr
Detection Angle:	120
Battery Type:	Li-ion 18650, 3.7V, 7200mAh Battery
Charging Time:	6-7 Hours



IP65
RATING



2 YEAR
WARRANTY



CRI>80

FEATURES

- LED Solar floodlight designed with detachable twin pad and PIR sensor with 2 brightness modes
- Uses Solar Panel for efficient photovoltaic conversion and lengthy lifespan
- Monocrystalline silicone solar panel.
- On/Off Button with 3 levels of lighting(50 %-5w, 100%-10W and Turn off)
- Built with a USB port allowing you to charge your phone/device anywhere anytime.
- Solar Panel dimensions: 344.7x235.6x44.7mm
- Suitable for Pathways, Garden, Patio and similar outdoor environment



SOLAR FLOODLIGHTS

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide an extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 8674 - 930 938

[View more details](#)



PACKAGING

Gross Weight (Kgs): 2.031
Unit CBM: 0.0070875
Dimension: 231.9x166.3x33.5mm

MASTER BOX PACKAGING

Box Qty: 10
Qty Per Pallet: 200
Length (Box) mm: 70
Width (Box) mm: 375
Height (Box) mm: 270

LISTING DETAILS

Commodity Code: 9405403990
Ean Code: 3800157652629